



HF2-10S

HF2-15S

HF2-17S

- Scale and Corrosion Protection
- Removes 6 Heavy Metals
- Removes 28 Hazardous Chemicals
- >95% Microplastic Reduction
- >92% Chlorine Reduction
- EP Compatible Cartridge

(Available in Single, Double & Triple Stage)

HF2-S

High performance filtration for ice

SPECIFICATION

	10S	15S	17S
Capacity L	45,425	79,494	98,421
Micron Rating	0.5 Micron		
Flow Rate	7.6 LPM		
Max Pressure	30-125 PSI		
Max Temperature	4-38°C		

DIMENSIONS

	10S	15S	17S
Height mm	295	426	476
Depth mm	110	110	110

www.h2odirect.co.uk
 sales@h2odirect.co.uk
 +44 1892 669628

FLUUX
 by
MICROFILTER



FLUUX HF2-S PREMIUM SYSTEMS

PERFORMANCE DATA Certified by NSF

HF2-10S FILTER SYSTEM

Claim	Influent Challenge Concentration	Average Reduction	Reduction Requirement	Max Permissible Product Water Concentration
Chlorine Taste and Odor	2.0mg/L ± 10%	92.2%	≥ 50%	N/A
Nominal Particulate Class1 >0.5µm to <1µm	At least 10,000 particles/mL	>97.6%	≥ 85%	N/A
Cyst	Min 50,000 cysts/L	>99.99%	≥ 99.95%	N/A
Microplastics	At least 10,000 particles/mL	>97.6%	≥ 85%	N/A

HF2-15S/17S FILTER SYSTEMS

Claim	Influent Challenge Concentration	Average Reduction	Reduction Requirement	Max Permissible Product Water Concentration
Chlorine Taste and Odor	2.0mg/L ± 10%	92.2%	≥ 50%	N/A
Nominal Particulate Class1 >0.5µm to <1µm	At least 10,000 particles/mL	>97.6%	≥ 85%	N/A
Cyst	Min 50,000 cysts/L	>99.99%	≥ 99.95%	N/A
Turbidity	11±1NTU	97.9%	N/A	0.5 NTU
Microplastics	At least 10,000 particles/mL	>97.6%	≥ 85%	N/A

MICROFILTER



System Tested and Certified by NSF International against NSF/ANSI 42 & 53 & 401 for the reduction of chlorine, Taste and Odor, Nominal Particulate Class1, Cyst and Microplastics.

System Tested and Certified by NSF International against NSF/ANSI 42 & 53 & 401 for the reduction of chlorine, Taste and Odor, Nominal Particulate Class1, Turbidity, Cyst and Microplastics.